



ZENVISION GmbH

Front view:



T +49 30 473 776 20

F +49 30 473 776 29

info@zenvision.de

ZENDOME.1000

The geodesic premium league. The incredible space embodies elegance with the impressive cupola rising to 17,5 m. Envisioning new dimensions, simply possible by German engineering!

Top view: ifting brackets with ventilation openings 35 m

17,70 m-	
4,20 m-	

Prenzlauer Promeande 189

D-13198 Berlin

www.zenvision.de

35 m
17,70 m
962 m²
1.924 m²
11.220 m³

ENTRANCE SETTINGS	
Entry	1 / optional 5
Width	1,80 m
Width (Circular membrane entry, measured at the centre	3,94 m
Height of the entry	3,20 m
Membrane entrance	1 / optional 5
Door system (optional)	5
Height of entrance with door	2,10 m
Width of entrance with door	0,89 + 0,89 m / 1,25 + 0,53 m
Door wings	2

WINDOW SETTINGS	
Round windows	3
Round windows (transparent or white)	3
Top round windows (ventilation openings)	5
AC-openings	3

MATERIAL & DETAILS	
Number of different struts	9
Min. length of struts	2.645 mm
Max. length of struts	3.591 mm
Diameter of struts	48,3 mm and 88,9 mm
Material thickness	2 mm and 4 mm
Number of structure feet	30
Membrane material	PVC Coated Polyester Fabrics

SAFETY	
Windloads (dynamic pressure q = kN/m² according to DIN 4112)	0,8
Dynamic pressure is about (Beaufort)	12 / violent storm
Extra loads (Please take note of the specification of loads)	3.000-6.000
Number of extra loads contact points	5-10

LOAD PARAMETERS	
Structure	18.500 kg
Structure feet	800 kg
Membrane	2.500 kg
Entrance	400 kg
Door	97 kg
Complete	22.297 kg

27.471 kg
21 m
m, stackable 11 + 7
e system 22.764 kg
em 234 kg and 70 kg
4x1,15x1,14m and 1,34x1,15x0,57m
1
4.550 kg
2.050 kg
6,00 x 2,30 x 2,24 m
1
157 kg
60 kg
2,35 x 2,00 x 0,35 m

5 - 7 days
3 - 5 days
8 - 10
7
min. 45 m / 30 m

NOTES:

- The construction time is timed with an experienced team.
 For first construction calculate double the time.
- \bullet Anchoring according to static calculations (earth anchors, heavy-load floor system or loads) necessary.
- All sizes, weights and volumes listed in this table are rounded approximations and may deviate due to varying materials or production processes.

Stand: Dec. 2017








ZENDOME.1000 / DOORWAY

From the very first touch of the material and entrance through the huge stargate you feel impressed. Smooth gliding doors with a perfect sound will support your event and amaze your guests right from the beginning.

Front view:



ENTRANCE SETTINGS	
Entry	1 (5)
Width, measured at floor-level	3,30 m
Width, measured at the centre	3,94 m
Height of the entry	3,20 m
Membrane entrance	1 (5)

DOOR SYSTEM (OPTIONAL)	
Height of entrance with door	2,10 m
Width of entrance with door	1,25 + 0,53 m / 0,89 + 0,89 m
Width (with door, measured at floor le	vel) 1,78 m
Door wings	2

ZENVISION GmbH Prenzlauer Promeande 189

D-13198 Berlin www.zenvision.de T +49 30 473 776 20 F +49 30 473 776 29 info@zenvision.de

Section:



MATERIAL & DETAILS	
Anchor plates (Optional)	Steel, galvanized
Foot door	Stainless steel, powder-coated
Vertical and horizontal poles	Stainless steel, powder-coated
Hub and tube connectors	Stainless steel, powder-coated
Special struts	Stainless steel, powder-coated
Door profiles	Aluminium
Door filling	Makrolon® clear / white
Door closer	yes
Push bar	yes

LOAD PARAMETERS	
Weight door	97 kg
Measurements transport box door (one door)	2,35 x 2,00 x 0,35 m
Weight / volume transport box door (one door)	60 kg / 1,65 m ³
Total weight / volume	157 kg / 1,65 m³
Weight entrance	400 kg
Loading	on frame stanchions








ZENDOME.1000 / LOGISTIC AND STORAGE


Prioritizing protection and process optimization, storage & logistic system are to ease operations, the key factors for cost-cutting. Increase profitability and secure your investments by keeping the maximum mobility up.

FRAME STANCHION, longitudinal section:




FRAME STANCHION ZD.1000	
Number of frame stanchions	11
Dimensions	3,84 x 1,15 x 1,14 m
Tare weight / volume	234 kg / 5,03 m³

SPINDLE STANCHION, longitudinal section:



SPINDLE STANCHION	
Number of spindle stanchions	2
Dimensions	1,34 x 1,15 x 0,57 m
Tare weight / volume	70 kg / 0,88 m³

FOOT STANCHION, longitudinal section:




FOOT STANCHION	
Number of foot stanchions	5
Dimensions	1,34 x 1,15 x 0,57 m
Tare weight / volume	70 kg / 0,88 m³

${\sf ZENVISION} \; {\sf GmbH}$


Prenzlauer Promeande 189 D-13198 Berlin www.zenvision.de

T +49 30 473 776 20 F +49 30 473 776 29 info@zenvision.de


FRAME STANCHION, cross section:



SPINDLE STANCHION, cross section:



FOOT STANCHION, cross section:



TRANSPORT BOXES WITH LID	
Number of transport boxes per foot stanchion	4
Dimension of transport box	0,40 x 0,30 x 0,22 m

Stand: Dec. 2017








ZENDOME.1000 / LOGISTIC AND STORAGE

The key to enhance the use of space and cutting cost is the storage & logistic system optimized for ideal container packaging. Whether by sea, air cargo or on the road, ZENDOME systems are perfectly packed.

MEMBRANE BOX, longitudinal section:



MEMBRANE BOX	
Number of Membrane boxes	1
Dimensions	6,00 x 2,30 x 2,24 m
Tare weight / volume	2.050 kg / 30,91 m ³

DOOR STANCHION, longitudinal section:




DOOR STANCHION	
Number of doors (maximum)	3
Dimensions (with frame)	2,42 x 1,15 x 2,27 m
Tare weight / volume (with frame)	292 kg / 6,31 m³

ZENVISION GmbH Prenzla

Prenzlauer Promeande 189 D-13198 Berlin www.zenvision.de T +49 30 473 776 20 F +49 30 473 776 29 info@zenvision.de

MEMBRANE BOX, front view:



DOOR STANCHION, cross section:

